

PRODUCT SPECIFICATION



LIBNA PRINT H

Printing paper, improved newsprint; made mainly from recycled fibres.

PROPERTY		UNIT	VALUE						
Grammage	ISO 536	g/m²	48.8	52	55	60	70	80	±2%
Specific volume	ISO 534	cm³/g	1.45–1.55						
Ash	ISO 1762	%	13						*
Moisture	ISO 287	%	7.0						*
Breaking strength	ISO 1924	N	35						*
Opacity	ISO 2471	%	91	93	94		95		*
Brightness (R 457)	ISO 2470	%	70						*
Colour	ISO 5631-2								
L			87						*
а			0.0						*
b			0.0						*
Cobb H ₂ O (60s)	ISO 535	g/m²	35						*

^{*} Typical values

OTHER CHARACTERISTICS

Reel dimensions:

- a) width (cm): 25-196 (combination of max. 13 reels)
- b) diameter (mm): max. 1250

Reel marks:

- a) inner side: unwinding direction mark
- b) joints marked: max. 2 per reel
- c) outer side: producer's name, paper grade, order, reel No., grammage (g/m²), reel width & diameter (cm), reel length (m), core diameter (cm), gross weight (kg), PM, PO, date

Sheet dimensions:

A1 (B1) - A0 deviations according to the ISO 216 Standard

Pallet marks:

producer's name, paper grade, order, pallet No., sheet size (mm), grain direction, grammage (g/m^2) , number of sheets, PO, theor. & gross & net weight (kg)

APPLICATION

For office and school supplies: writing pads, notebooks, workbooks. For newspapers, periodicals, advertising materials and books in black&white and multi-colour heat-set and cold-set offset printing; also for sheet-fed printing.

PACKING

Reels wrapped in multiple layers of waterproof paper laminate.

NOTES

Ecological grade; **ECF**; made from recycled fibres obtained from recovered paper in deinking process. **FSC®**: FSC Mix Credit certified product can be provided upon request.

Quality Control Manager Aleksandra Račič Kozmus

Technology & Development Manager Danijel Oštir