

Offset extra



Uncoated, surface-sized printing paper based on 100 % recycled and deinked fibres

TYPICAL END USES	BENEFITS	FINISH	PRINTING METHODS
Brochures, leaflets, reports, catalogues, calendar, school and writing books	Good opacity Treated for ink fastness*	mat surface	Heatset Offset Digital Letterpress

Substance	Standard	Unit	Tolerance	45	48,8	50	52	55	60	70	80	90	100*	120*
Basis weight	ISO 536	g/m ²	± 4%	45	48,8	50	52	55	60	70	80	90	100	120
Bulk	ISO 534	cm ³ /g	± 0,05	1,27	1,27	1,27	1,27	1,27	1,27	1,27	1,27	1,27	1,27	1,27
Brightness	ISO 2470	%	± 3	70	70	70	70	70	70	70	70	70	70	70
Opacity	ISO 2471	%	min.	87	88	89	90	91	93	94	95	96	95	95

*on demand

REEL SPECIFICATIONS	ENVIRONMENT	CERTIFICATES
Cores: 70 mm, 76 mm, 150 mm, 152 mm Trimmed width: 3870 mm Width: min. 340 mm, max. 2860 mm Diameters: min. 1000 mm, max. 1250 mm Max. Weight: 3900 kg Available in sheet formats upon request	Based on 100 % recycled fibre No chlorine bleaching in production process Recyclable paper Recyclable packaging materials	FSC® PEFC™ Blauer Engel

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50 % relative humidity and room temperature between 19 °C and 23 °C.
- If the paper is stored in non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.

Manufactured at

Kübler & Niethammer Papierfabrik Kriebstein GmbH
Bauhofstraße 1
OT Kriebethal, 09648 Kriebstein, Germany
Tel +49 (0) 34327 97-50
info@k-n-paper.de